

[Previous Doc](#)[Next Doc](#)[Go to Doc#](#)[First Hit](#)Generate Collection

L8: Entry 7 of 10

File: JPAB

Jul 31, 1985

PUB-NO: JP360145431A

DOCUMENT-IDENTIFIER: JP 60145431 A

TITLE: SPEED RATIO INCREASE CONTROL METHOD OF HYDROMECHANICAL SPEEDCHANGE/STEERING MECHANISM UNDER ACCELERATION

PUBN-DATE: July 31, 1985

INVENTOR-INFORMATION:

NAME

COUNTRY

YANAGISAWA, MAMORU

AKIYAMA, MITSURU

KONISHI, HIDEYUKI

MARUYAMA, RYOICHI

MASUTANI, FUMIO

HATAYAMA, KEIJI

NISHIJIMA, TAKAYOSHI

ASSIGNEE-INFORMATION:

NAME

COUNTRY

TECH RES & DEV INST OF JAPAN DEF AGENCY

KOMATSU LTD

APPL-NO: JP59000734

APPL-DATE: January 9, 1984

US-CL-CURRENT: 417/216

INT-CL (IPC): F02D 29/04; B60K 26/04; B60K 41/12

ABSTRACT:

PURPOSE: To achieve acceleration matching to the operational feeling by controlling the speed change ratio such that the acceleration of an engine associated with hydromechanical speedchange gear will return within predetermined range upon exceeding over said range thereby increasing the rotation of output shaft together with the engine rotation under acceleration.

CONSTITUTION: An engine 2 and output shafts 4, 5 are coupled through a hydromechanical speed changer 1 to drive hydraulic pumps 6, 7 thus to feed pressure oil to hydraulic motors 8, 9. A controller 28 will operate the acceleration from a signal fed from an engine rotation detector 15. If it has exceeded over predetermined level, said motors 8, 9 are driven to increase the speedchange ratio thus to increase the engine load and to bring the engine rotation increasing rate constant while simultaneously increase the car speed.

COPYRIGHT: (C)1985, JPO&Japio